

WEEBILL-S Camera Compatibility List


Updated on March 23th, 2020 (for stabilizer firmware V1.90)

V1.40

Camera Model	Photo		Video		Live Preview	Shutter Speed Adjustment		Aperture Adjustment		ISO Adjustment		EV Adjustment		Electronic Zoom	Halfway Press Shutter Button to Autofocus	Electronic Follow Focus (Focus Wheel)	Camera Control Cable Type	Camera Firmware Version
	Save	Playback	Save	Playback		Photo Mode	Video Mode	Photo Mode	Video Mode	Photo Mode	Video Mode	Photo Mode	Video Mode					
Sony a9	√	√	√	√	-	-	-	-	-	-	-	-	-	√	-		Micro USB to Multi USB	V5.00
Sony a7R4	√	√	√	√	-	-	-	-	-	-	-	-	-	√	-		Micro USB to Multi USB	V1.00
Sony a7R3	√	√	√	√	-	-	-	-	-	-	-	-	-	√	-		Micro USB to Multi USB	V3.01
Sony a7M3	√	√	√	√	-	-	-	-	-	-	-	-	-	√	-		Micro USB to Multi USB	V4.00
Sony a7R2	√	√	√	√	-	-	-	-	-	-	-	-	-	√	-		Micro USB to Multi USB	V3.00
Sony a7M2	√	√	√	√	-	-	-	-	-	-	-	-	-	√	-		Micro USB to Multi USB	V3.00
Sony a7S2	√	√	√	√	-	-	-	-	-	-	-	-	-	√	-		Micro USB to Multi USB	V4.00
Sony a6600	√	√	√	√	-	-	-	-	-	-	-	-	-	√	-		Micro USB to Multi USB	V1.00
Sony a6500	√	√	√	√	-	-	-	-	-	-	-	-	-	√	-		Micro USB to Multi USB	V1.06
Sony a6400	√	√	√	√	-	-	-	-	-	-	-	-	-	√	-		Micro USB to Multi USB	V2.00
Sony a6300	√	√	√	√	-	-	-	-	-	-	-	-	-	√	-		Micro USB to Multi USB	V2.01
Sony a6100	√	√	√	√	-	-	-	-	-	-	-	-	-	√	-		Micro USB to Multi USB	V1.00
Sony a6000	√	√	√	√	-	-	-	-	-	-	-	-	-	√	-		Micro USB to Multi USB	v3.21
Panasonic GH5	√	√	√	√	-	√	√	√	√	√	√	√	√		√	√	Micro USB to Type-C USB	V2.5
Panasonic GH5S	√	√	√	√	-	√	√	√	√	√	√	√	√		√	√	Micro USB to Type-C USB	V1.3
Panasonic S1	√	√	√	√	-	√	√	√	√	√	√	√	√		√	√	Micro USB to Type-C USB	V1.2
Panasonic S1H	√	√	√	√	-	√	√	√	√	√	√	√	√		√	√	Micro USB to Type-C USB	V0.53
Canon 5D3	√	√	√	√	√	√	√	√	√	√	√	√	√		Unavailable in Live View mode	√	Micro USB to Mini USB	V1.3.5
Canon 5D4	√	√	√	√	√	√	√	√	√	√	√	√	√		Unavailable in Live View mode	√	Micro USB to Micro USB	V1.0.4
Canon 5DS	√	√	√	√	√	√	√	√	√	√	√	√	√		Unavailable in Live View mode	√	Micro USB to Micro USB	V1.1.1
Canon 5DS R	√	√	√	√	√	√	√	√	√	√	√	√	√		Unavailable in Live View mode	√	Micro USB to Micro USB	V1.1.2R
Canon 6D	√	√	√	√	√	√	√	√	√	√	√	√	√		Unavailable in Live View mode	√	Micro USB to Mini USB	V1.1.8
Canon 6D2	√	√	√	√	√	√	√	√	√	√	√	√	√		Unavailable in Live View mode	√	Micro USB to Mini USB	V1.0.4
Canon 80D	√	√	√	√	√	√	√	√	√	√	√	√	√		Unavailable in Live View mode	√	Micro USB to Mini USB	V1.0.2
Canon 90D	√	√	√	√	√	√	√	√	√	√	√	√	√		Unavailable in Live View mode	√	Micro USB to Micro USB	V1.0.0
Canon M50	√	√	√	√	-	√	√	√	√	√	√	√	√		-	-	Micro USB to Micro USB	V1.0.3
Canon EOS R	√	√	√	√	-	√	√	√	√	√	√	√	√		-	√	Micro USB to Type-C USB	V1.3.0
Canon EOS RP	√	√	√	√	-	√	√	√	√	√	√	√	√		-	√	Micro USB to Type-C USB	V1.3.0
Nikon D850	√	√	√	√	√	√	√	√	√	√	√	√	√		√	√	Micro USB to Micro USB	V1.02
Nikon Z6	√	√	√	√	-	√	√	√	√	√	√	√	√		√	√	Micro USB to Type-C USB	V2.01

Camera Model	Photo		Video		Live Preview	Shutter Speed Adjustment		Aperture Adjustment		ISO Adjustment		EV Adjustment		Electronic Zoom	Halfway Press Shutter Button to Autofocus	Electronic Follow Focus (Focus Wheel)	Camera Control Cable Type	Camera Firmware Version
	Save	Playback	Save	Playback		Photo Mode	Video Mode	Photo Mode	Video Mode	Photo Mode	Video Mode	Photo Mode	Video Mode					
Nikon Z7	√	√	√	√	-	√	√	√	√	√	√	√	√		√	√	Micro USB to Type-C USB	V2.01
Nikon Z50	√	√	√	√	-	√	√	√	√	√	√	√	√		√	√	Micro USB to Type-C USB	V1.00
Olympus OM-D E-M1 Mark II	√	√	√	√	-	√	√	√	√	√	√	√	-		√	√	Micro USB to Type-C USB	V3.1
Fujifilm X-T3	√	√	√	√	-	√	-	-	-	√	√	√	√		√	-	Micro USB to Type-C USB	V3.10

Note:

1. This table will be updated in line with firmware update and is subject to change without prior notice;
2. For Sony cameras, after connecting stabilizer and camera with control cable, power on the stabilizer and then the camera. Make sure the camera has sufficient power to operate. Optical zoom control is available on the stabilizer when used with motorized lens. Digital zoom control is available on the stabilizer when used with non-motorized lens. Please select zoom option in your camera's settings;
3. With Panasonic cameras, please choose PC (Tether) for your camera's USB mode;
4. When shooting panorama or timelapse, it is recommended to turn off the camera's auto review (Sony) or image confirmation (Canon) or image review (Nikon) to reduce system latency.
5. In Photo mode of Fujifilm X-T3, camera parameter control from camera is disabled and you can only adjust camera parameter via stabilizer. Click LV button of stabilizer to resume parameter control of your camera and click LV button again to return to stabilizer control;
6. For Fujifilm X-T3, after connecting to the stabilizer, single click LV button before switching the camera from Photo mode to Video mode; Single click LV button after switching the camera from Video mode to Photo mode;
7. After connecting Olympus cameras to WEEBILL-S, there will be a prompt on camera screen for you to choose USB mode. Please choose[] (PC control) and turn camera mode dial to P, A, S or M mode.



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Canon	5DS	EF 11-24mm f/4L USM	Camera and lens	-				
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		EF 16-35mm f/4L IS USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
		EF 16-35mm f/2.8L III USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 17-40mm f/4L USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 24-70mm f/2.8L II USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
		EF 24-70mm f/4L IS USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 24-105mm f/4L IS II USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	-	-	Can be balanced at any focal length; No need to remove eyepiece cap		
		EF 24-105mm f/3.5-5.6 IS STM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	-			Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Canon	5DS	EF 24mm f/1.4L II USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 35mm f/1.4L II USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 50mm f/1.4 USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 85mm f/1.4L IS USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 85mm f/1.8 USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)					
		Sigma 24-70mm f/2.8 DG HSM Art	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		Sigma 35mm f/1.4 DG HSM Art	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 50mm f/1.4 DG HSM Art	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Canon	5DS R	EF 11-24mm f/4L USM	Camera and lens	-				
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		EF 16-35mm f/4L IS USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
		EF 16-35mm f/2.8L III USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 17-40mm f/4L USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 24-70mm f/2.8L II USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the right	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the right	
		EF 24-70mm f/4L IS USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 24-105mm f/4L IS II USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the right	
			Camera, lens and servo motor (for zoom control)	-	-	Can be balanced at any focal length; No need to remove eyepiece cap		
		EF 24-105mm f/3.5-5.6 IS STM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	-			Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Canon	5DS R	EF 24mm f/1.4L II USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 35mm f/1.4L II USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 50mm f/1.4 USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 85mm f/1.2L II USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 85mm f/1.4L IS USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 85mm f/1.8 USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		Sigma 24-70mm f/2.8 DG HSM Art	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 35mm f/1.4 DG HSM Art	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 35mm f/1.4L II USM	Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for zoom control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Canon	5D Mark IV	EF 11-24mm f/4L USM	Camera and lens	-				
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		EF 16-35mm f/4L IS USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
		EF 16-35mm f/2.8L III USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 17-40mm f/4L USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 24-70mm f/2.8L II USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 24-70mm f/2.8L II USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the right	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the right	
		EF 24-70mm f/4L IS USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 24-105mm f/4L IS II USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the right	
			Camera, lens and servo motor (for zoom control)	-	-	Can be balanced at any focal length; No need to remove eyepiece cap		



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Canon	5D Mark IV	EF 24-105mm f/3.5-5.6 IS STM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 24mm f/1.4L II USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 35mm f/1.4L II USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 50mm f/1.4 USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 85mm f/1.4L IS USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 85mm f/1.8 USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 24-70mm f/2.8 DG HSM Art	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	-	-			
			Camera, lens and servo motor (for zoom control)	-	-			
		Sigma 35mm f/1.4 DG HSM Art	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 50mm f/1.4 DG HSM Art	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/Focus Motor	Installation Remark
Canon	5D Mark III	EF 11-24mm f/4L USM	Camera and lens	-				
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		EF 16-35mm f/4L IS USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
		EF 16-35mm f/2.8L III USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 17-40mm f/4L USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 24-70mm f/2.8L II USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the right	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the right	
		EF 24-70mm f/4L IS USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 24-105mm f/4L IS II USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the right	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
		EF 24-105mm f/3.5-5.6 IS STM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Canon	5D Mark III	EF 24mm f/1.4L II USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 35mm f/1.4L II USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 50mm f/1.2L USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap		
		EF 50mm f/1.4 USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 85mm f/1.4L IS USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 85mm f/1.8 USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 24-70mm f/2.8 DG HSM Art	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		Sigma 35mm f/1.4 DG HSM Art	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 50mm f/1.4 DG HSM Art	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 24-70mm f/4L IS USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 24-105mm f/4L IS II USM	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the right	
Camera, lens and servo motor (for zoom control)	√		-	Can be balanced at any focal length. Need to remove eyepiece cap				

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Canon	5D Mark III	EF 24-105mm f/3.5-5.6 IS STM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 24mm f/1.4L II USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 50mm f/1.2L USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 50mm f/1.4 USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Canon	6D Mark II	EF 85mm f/1.4L IS USM	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 85mm f/1.8 USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 24-70mm f/2.8 DG HSM Art	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	-	-			
			Camera, lens and servo motor (for zoom control)	-	-			
		Sigma 35mm f/1.4 DG HSM Art	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 50mm f/1.4 DG HSM Art	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/Focus Motor	Installation Remark
Canon	6D Mark II	EF 11-24mm f/4L USM	Camera and lens	-				
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		EF 16-35mm f/4L IS USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
		EF 16-35mm f/2.8L III USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 17-40mm f/4L USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 24-70mm f/2.8L II USM	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the right	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the right	
		EF 24-70mm f/4L IS USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 24-105mm f/4L IS II USM	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the right	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length. Need to remove eyepiece cap		
		EF 24-105mm f/3.5-5.6 IS STM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Canon	6D	EF 24mm f/1.4L II USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 35mm f/1.4L II USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 50mm f/1.2L USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 50mm f/1.4 USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 11-24mm f/4L USM	Camera and lens	-				
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		EF 16-35mm f/4L IS USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
		EF 16-35mm f/2.8L III USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 17-40mm f/4L USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 24-70mm f/2.8L II USM	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the right	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the right	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/Focus Motor	Installation Remark
Canon	6D	EF 24-70mm f/4L IS USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 24-105mm f/4L IS II USM	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the right	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length. Need to remove eyepiece cap		
		EF 24-105mm f/3.5-5.6 IS STM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 24mm f/1.4L II USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 35mm f/1.4L II USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 50mm f/1.2L USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 50mm f/1.4 USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 85mm f/1.4L IS USM	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 85mm f/1.8 USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 24-70mm f/2.8 DG HSM Art	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	-	-			
			Camera, lens and servo motor (for zoom control)	-	-			
Sigma 35mm f/1.4 DG HSM Art	Camera and lens	√	-	No need to remove eyepiece cap				
	Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side			



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Canon	6D	Sigma 50mm f/1.4 DG HSM Art	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Canon	90D	EF 11-24mm f/4L USM	Camera and lens	-				
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		EF 16-35mm f/4L IS USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 16-35mm f/2.8L III USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 17-40mm f/4L USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 24-70mm f/2.8L II USM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced between focal length 24-50mm. No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	-				
		EF 24-105mm f/4L IS II USM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced between focal length 24-50mm. No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	-				
		EF 24-105mm f/3.5-5.6 IS STM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Canon	90D	EF 24mm f/1.4L II USM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 35mm f/1.4L II USM	Camera and lens	√	-	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side
		EF 50mm f/1.4 USM	Camera and lens	√	-	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side
		EF 85mm f/1.4L IS USM	Camera and lens	√	-	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side
		EF 85mm f/1.8 USM	Camera and lens	√	-	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side
		Sigma 24-70mm f/2.8 DG HSM Art	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		Sigma 35mm f/1.4 DG HSM Art	Camera and lens	√	-	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side
		Sigma 50mm f/1.4 DG HSM Art	Camera and lens	√	-	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side
		Sigma 18-35mm f/1.8 DG HSM Art	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		Servo zoom & focus motor installed on the right
			Camera, lens and servo motor (for zoom control)	-				



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Canon	80D	EF 11-24mm f/4L USM	Camera and lens	-				
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		EF 16-35mm f/4L IS USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 16-35mm f/2.8L III USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 17-40mm f/4L USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 24-70mm f/2.8L II USM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced between focal length 24-50mm. No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	-				
		EF 24-105mm f/4L IS II USM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced between focal length 24-50mm. No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	-				
		EF 24-105mm f/3.5-5.6 IS STM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark	
Canon	80D	EF 24mm f/1.4L II USM	Camera and lens	√	-	No need to remove eyepiece cap			
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side		
		EF 35mm f/1.4L II USM	Camera and lens	√	-	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side	
		EF 50mm f/1.4 USM	Camera and lens	√	-	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side	
		EF 85mm f/1.4L IS USM	Camera and lens	√	-	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side	
		EF 85mm f/1.8 USM	Camera and lens	√	-	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side	
		Sigma 24-70mm f/2.8 DG HSM Art	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap			
			Camera, lens and servo motor (for focus control)	-					
			Camera, lens and servo motor (for zoom control)	-					
		Sigma 35mm f/1.4 DG HSM Art	Camera and lens	√	-	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side	
		Sigma 50mm f/1.4 DG HSM Art	Camera and lens	√	-	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap		Servo zoom & focus motor installed on either side	
		Sigma 18-35mm f/1.8 DG HSM Art	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap			
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		Servo zoom & focus motor installed on the right	
			Camera, lens and servo motor (for zoom control)	-					



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Canon	EOS R (Mount adapter EF-EOS R is needed for non-RF lens)	EF 11-24mm f/4L USM	Camera and lens	-				
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		EF 16-35mm f/4L IS USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 16-35mm f/2.8L III USM	Camera and lens	-				
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		EF 17-40mm f/4L USM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 24-70mm f/2.8L II USM	Camera and lens	-				
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		EF 24-70mm f/4L IS USM	Camera and lens	√	√	Can be balanced at focal length 24mm; Do not remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at focal length 24mm; Do not remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at focal length 24mm; Do not remove eyepiece cap	Servo zoom & focus motor installed on the left	
		EF 24-105mm f/4L IS II USM	Camera and lens	-				
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		EF 24-105mm f/3.5-5.6 IS STM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced between focal length 24-50mm. Do not remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	-				
EF 24mm f/1.4L II USM	Camera and lens	√	-	Do not remove eyepiece cap				
	Camera, lens and servo motor (for focus control)	√	-	Do not remove eyepiece cap	Servo zoom & focus motor installed on either side			
EF 35mm f/1.4L II USM	Camera and lens	√	-	Do not remove eyepiece cap				
	Camera, lens and servo motor (for focus control)	√	-	Do not remove eyepiece cap	Servo zoom & focus motor installed on either side			



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Canon	EOS R (Mount adapter EF-EOS R is needed for non-RF lens)	EF 50mm f/1.2L USM	Camera and lens	√	-	Do not remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Do not remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 50mm f/1.4 USM	Camera and lens	√	-	Do not remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Do not remove eyepiece cap	Servo zoom & focus motor installed on either side	
		EF 85mm f/1.4L IS USM	Camera and lens	√	-	Do not remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	-				
		EF 85mm f/1.8 USM	Camera and lens	√	-	Do not remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Do not remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 24-70mm f/2.8 DG HSM Art	Camera and lens	-				
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		Sigma 35mm f/1.4 DG HSM Art	Camera and lens	√	-	Do not remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Do not remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 50mm f/1.4 DG HSM Art	Camera and lens	√	-	Do not remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Do not remove eyepiece cap	Servo zoom & focus motor installed on either side	
		RF 15-35mm f/2.8 L IS USM	Camera and lens	√	√			
			Camera, lens and servo motor (for focus control)	-	√	Do not remove eyepiece cap	Servo zoom & focus motor installed on either side	The eyepiece cap may slightly interfere with the roll axis motor when a follow focus motor is mounted on the gimbal but it won't impair the use of the gimbal.
			Camera, lens and servo motor (for zoom control)	-	√	Do not remove eyepiece cap	Servo zoom & focus motor installed on either side	The eyepiece cap may slightly interfere with the roll axis motor when a follow focus motor is mounted on the gimbal but it won't impair the use of the gimbal.
		RF28-70mm F2 L	Camera and lens	-				
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
RF50mm F1.2 L USM	Camera and lens	√	√	Do not remove eyepiece cap				
	Camera, lens and servo motor (for focus control)	√	√	Do not remove eyepiece cap	Servo zoom & focus motor installed on either side			
	Camera, lens and servo motor (for zoom control)							



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark	
Canon	EOS RP (Mount adapter EF-EOS R is needed for non-RF lens)	EF 11-24mm f/4L USM	Camera and lens	-					
			Camera, lens and servo motor (for focus control)	-					
			Camera, lens and servo motor (for zoom control)	-					
		EF 16-35mm f/4L IS USM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap			
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side		
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side		
		EF 16-35mm f/2.8L III USM	Camera and lens	√	√	Can be balanced between focal length 16mm. Do not remove eyepiece cap			Eyeiece cap slightly rub against the camera
			Camera, lens and servo motor (for focus control)	-					
			Camera, lens and servo motor (for zoom control)	-					
		EF 17-40mm f/4L USM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap			
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side		
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side		
		EF 24-70mm f/2.8L II USM	Camera and lens	√	√	Can be balanced at focal length 24mm; Do not remove eyepiece cap			
			Camera, lens and servo motor (for focus control)	-					
			Camera, lens and servo motor (for zoom control)	-					
		EF 24-70mm f/4L IS USM	Camera and lens	√	√	Can be balanced at focal length 24mm; Do not remove eyepiece cap			
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at focal length 24mm; Do not remove eyepiece cap	Servo zoom & focus motor installed on either side		Eyeiece cap slightly rub against the camera
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at focal length 24mm; Do not remove eyepiece cap	Servo zoom & focus motor installed on the left		Eyeiece cap slightly rub against the camera
		EF 24-105mm f/4L IS II USM	Camera and lens	√	√	Can be balanced at focal length 24mm; Do not remove eyepiece cap			
			Camera, lens and servo motor (for focus control)	-					
			Camera, lens and servo motor (for zoom control)	-					
		EF 24-105mm f/3.5-5.6 IS STM	Camera and lens	√	√	Can be balanced between focal length 24-70mm; Do not remove eyepiece cap			
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at focal length 24mm; Do not remove eyepiece cap	Servo zoom & focus motor installed on the left		
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at focal length 24mm; Do not remove eyepiece cap	Servo zoom & focus motor installed on the left		



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Canon	EOS RP (Mount adapter EF-EOS R is needed for non-RF lens)	EF 24mm f/1.4L II USM	Camera and lens	√	√	Do not remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Do not remove eyepiece cap	Servo zoom & focus motor installed on the left	
		EF 35mm f/1.4L II USM	Camera and lens	√	√	Do not remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Do not remove eyepiece cap	Servo zoom & focus motor installed on the left	
		EF 50mm f/1.2L USM	Camera and lens	√	√	Do not remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Do not remove eyepiece cap	Servo zoom & focus motor installed on the left	
		EF 50mm f/1.4 USM	Camera and lens	√	√	Do not remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Do not remove eyepiece cap	Servo zoom & focus motor installed on the left	
		EF 85mm f/1.4L IS USM	Camera and lens	√	√	Do not remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Do not remove eyepiece cap	Servo zoom & focus motor installed on the left	Eye-piece cap slightly rub against the camera
		Sigma 24-70mm f/2.8 DG HSM Art	Camera and lens	-				
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		Sigma 35mm f/1.4 DG HSM Art	Camera and lens	√	√	Do not remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Do not remove eyepiece cap	Servo zoom & focus motor installed on the left	
		Sigma 50mm f/1.4 DG HSM Art	Camera and lens	√	√	Do not remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Do not remove eyepiece cap	Servo zoom & focus motor installed on the left	
		RF 15-35mm f/2.8 L IS USM	Camera and lens					
			Camera, lens and servo motor (for focus control)	-	√	Do not remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	-	√	Do not remove eyepiece cap	Servo zoom & focus motor installed on the left	
		RF28-70mm F2 L	Camera and lens	-				
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		RF50mm F1.2 L USM	Camera and lens	√	√	Do not remove eyepiece cap		
Camera, lens and servo motor (for focus control)	√		√	Do not remove eyepiece cap	Servo zoom & focus motor installed on the left			



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Nikon	D850	AF-S NIKKOR 14-24mm f/2.8G ED	Camera and lens	-				
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		AF-S NIKKOR 16-35mm f/4G ED VR	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
		AF-S NIKKOR 24-70mm f/2.8E ED VR	Camera and lens	-	√			
			Camera, lens and servo motor (for focus control)	-	√			
			Camera, lens and servo motor (for zoom control)	-				
		AF-S NIKKOR 24-70mm f/2.8G ED	Camera and lens	-	√			
			Camera, lens and servo motor (for focus control)	-	√			
			Camera, lens and servo motor (for zoom control)	-				
		AF-S NIKKOR 24-120mm f/4G ED VR	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
		AF-S NIKKOR 24mm f/1.4G ED	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		AF-S NIKKOR 24mm f/1.8G ED	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		AF-S NIKKOR 35mm f/1.4G	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		AF-S NIKKOR 50mm f/1.4G	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		AF-S NIKKOR 85mm f/1.4G	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		AF-S NIKKOR 85mm f/1.8G	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
Sigma 24 70mm f/2.8L DG	Camera and lens	√	-	No need to remove eyepiece cap				
	Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side			
Sigma 35mm F1.4 DG	Camera and lens	√	-	No need to remove eyepiece cap				
	Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side			



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Nikon	D850	Sigma 50mm F1.4 DG	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Nikon	D750	AF-S NIKKOR 14-24mm f/2.8G ED	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	-	-			
		AF-S NIKKOR 16-35mm f/4G ED VR	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		AF-S NIKKOR 24-70mm f/2.8E ED VR	Camera and lens	-	-			
			Camera, lens and servo motor (for focus control)	-	-			
			Camera, lens and servo motor (for zoom control)	-	-			
		AF-S NIKKOR 24-70mm f/2.8G ED	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	-	-			
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
		AF-S NIKKOR 24mm f/1.4G ED	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		AF-S NIKKOR 24mm f/1.8G ED	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		AF-S NIKKOR 35mm f/1.4G	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		AF-S NIKKOR 50mm f/1.4G	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		AF-S NIKKOR 85mm f/1.4G	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark	
Nikon	D750	AF-S NIKKOR 85mm f/1.8G	Camera and lens	√	-	No need to remove eyepiece cap			
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side		
		Sigma 24 70mm f/2.8L DG	Camera and lens	√	-	No need to remove eyepiece cap			
			Camera, lens and servo motor (for focus control)	-	-				
		Sigma 35mm F1.4 DG	Camera, lens and servo motor (for zoom control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side		
			Camera and lens	√	-	No need to remove eyepiece cap			
		Sigma 50mm F1.4 DG	Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side		
			Camera and lens	√	-	No need to remove eyepiece cap			
				Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
				Camera and lens	√	-	No need to remove eyepiece cap		

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Nikon	Z6	NIKKOR Z 24-70mm f/2.8S	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		NIKKOR Z 24-70mm f/4S	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	-	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		NIKKOR Z 35mm f/1.8S	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		NIKKOR Z 50mm f/1.8S	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		AF-S NIKKOR 14-24mm f/2.8G ED	Camera and lens	-	-			
			Camera, lens and servo motor (for focus control)	-	-			
			Camera, lens and servo motor (for zoom control)	-	-			
		AF-S NIKKOR 16-35mm f/4G ED VR	Camera and lens	√	-			
			Camera, lens and servo motor (for focus control)	-	-			
			Camera, lens and servo motor (for zoom control)	-	-			



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark	
Nikon	Z6	AF-S NIKKOR 24-70mm f/2.8E ED VR	Camera and lens	-					
			Camera, lens and servo motor (for focus control)	-					
			Camera, lens and servo motor (for zoom control)	-					
		AF-S NIKKOR 24-70mm f/2.8G ED	Camera and lens	-					
			Camera, lens and servo motor (for focus control)	-					
			Camera, lens and servo motor (for zoom control)	-					
		AF-S NIKKOR 24-120mm f/4G ED VR	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap			
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced between focal length 24-85mm. Need to remove eyepiece cap			
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced between focal length 24-85mm. Need to remove eyepiece cap			
		AF-S NIKKOR 24mm f/1.4G ED	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap			
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length. Need to remove eyepiece cap			
		AF-S NIKKOR 24mm f/1.8G ED	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap			
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length. Need to remove eyepiece cap			
		AF-S NIKKOR 35mm f/1.4G	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap			
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length. Need to remove eyepiece cap			
		AF-S NIKKOR 50mm f/1.4G	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap			
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length. Need to remove eyepiece cap			
		Sigma 24 70mm f/2.8L DG	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap			
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced between focal length 24-40mm. Need to remove eyepiece cap			
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced between focal length 24-40mm. Need to remove eyepiece cap			
		Sigma 35mm F1.4 DG	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap			
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length. Need to remove eyepiece cap			
		Sigma 50mm F1.4 DG	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap			
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length. Need to remove eyepiece cap			

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark	
Nikon	Z7	NIKKOR Z 24-70mm f/2.8S	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap			
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side		
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side		
		NIKKOR Z 24-70mm f/4S	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap			
			Camera, lens and servo motor (for focus control)	-	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side		
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side		



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Nikon	Z7	NIKKOR Z 35mm f/1.8S	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		NIKKOR Z 50mm f/1.8S	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		AF-S NIKKOR 14-24mm f/2.8G ED	Camera and lens	-				
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		AF-S NIKKOR 16-35mm f/4G ED VR	Camera and lens	√	-			
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		AF-S NIKKOR 24-70mm f/2.8E ED VR	Camera and lens	-				
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		AF-S NIKKOR 24-70mm f/2.8G ED	Camera and lens	-				
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				
		AF-S NIKKOR 24-120mm f/4G ED VR	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced between focal length 24-85mm. Need to remove eyepiece cap		
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced between focal length 24-85mm. Need to remove eyepiece cap		
		AF-S NIKKOR 24mm f/1.4G ED	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length. Need to remove eyepiece cap		
		AF-S NIKKOR 24mm f/1.8G ED	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length. Need to remove eyepiece cap		
		AF-S NIKKOR 35mm f/1.4G	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length. Need to remove eyepiece cap		
		AF-S NIKKOR 50mm f/1.4G	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length. Need to remove eyepiece cap		
		Sigma 24 70mm f/2.8L DG	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced between focal length 24-40mm. Need to remove eyepiece cap		
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced between focal length 24-40mm. Need to remove eyepiece cap		
Sigma 35mm F1.4 DG	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap				
	Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length. Need to remove eyepiece cap				
Sigma 50mm F1.4 DG	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap				
	Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length. Need to remove eyepiece cap				



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A9	FE 16-35mm F2.8 GM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 16-35mm F4 ZAISS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 12-24mm F4 G	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24mm f1.4GM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24-70mm F2.8 GM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced between focal length 24-50mm. Need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced between focal length 24-50mm. Need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24-70mm F4 ZA OSS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 28mm F2	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 50mm F1.8	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 85mm F1.4 GM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A9	Distagon T* FE 35mm F1.4 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
		Sonnar T* FE 35mm F2.8 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on the right	
		Sonnar® T* FE 55mm F1.8 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 10–18mm F4 OSS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E PZ 18–105mm F4 G OSS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 18–200mm F3.5–6.3 OSS LE	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
		Sigma 30mm f/1.4 DC DN	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 50mm f/1.4 DG	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
		Tamron 28-75mm f/2.8	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
Camera, lens and servo motor (for zoom control)	√		√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left			



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A9	sigma18-35mm f/1.8 DC HSM Art (Canon lens adapter)	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A7M2	FE 16-35mm F2.8 GM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 16-35mm F4 ZAISS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 12-24mm F4 G	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24mm f1.4GM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24-70mm F2.8 GM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera
		FE 24-70mm F4 ZA OSS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A7M2	FE 28mm F2	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 50mm F1.8	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 85mm F1.4 GM	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Distagon T* FE 35mm F1.4 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar T* FE 35mm F2.8 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar® T* FE 55mm F1.8 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 10–18mm F4 OSS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
		E PZ 18–105mm F4 G OSS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 18–200mm F3.5–6.3 OSS LE	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 30mm f/1.4 DC DN	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A7M2	Sigma 50mm f/1.4 DG	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Tamron 28-75mm f/2.8	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		sigma18-35mm f/1.8 DC HSM Art (Canon lens adapter)	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	-	-			
			Camera, lens and servo motor (for zoom control)	-	-			

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A7R2	FE 16-35mm F2.8 GM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 16-35mm F4 ZAISS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 12-24mm F4 G	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24mm f1.4GM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24-70mm F2.8 GM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A7R2	FE 24-70mm F4 ZA OSS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 28mm F2	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 50mm F1.8	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 85mm F1.4 GM	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Distagon T* FE 35mm F1.4 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar T* FE 35mm F2.8 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar® T* FE 55mm F1.8 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 10-18mm F4 OSS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
		E PZ 18-105mm F4 G OSS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A7R2	E 18-200mm F3.5-6.3 OSS LE	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 30mm f/1.4 DC DN	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 50mm f/1.4 DG	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Tamron 28-75mm f/2.8	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		sigma18-35mm f/1.8 DC HSM Art (Canon lens adapter)	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	-	-			
			Camera, lens and servo motor (for zoom control)	-	-			

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A7S2	FE 16-35mm F2.8 GM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 16-35mm F4 ZA/ISS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 12-24mm F4 G	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A7S2	FE 24mm f1.4GM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24-70mm F2.8 GM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera
		FE 24-70mm F4 ZA OSS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 28mm F2	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 50mm F1.8	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 85mm F1.4 GM	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Distagon T* FE 35mm F1.4 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar T* FE 35mm F2.8 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar® T* FE 55mm F1.8 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 10-18mm F4 OSS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A7S2	E PZ 18-105mm F4 G OSS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 18-200mm F3.5-6.3 OSS LE	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 30mm f/1.4 DC DN	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 50mm f/1.4 DG	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Tamron 28-75mm f/2.8	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		sigma18-35mm f/1.8 DC HSM Art (Canon lens adapter)	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A7M3	FE 16-35mm F2.8 GM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 16-35mm F4 ZAISS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 12-24mm F4 G	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24mm f1.4GM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24-70mm F2.8 GM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera
		FE 24-70mm F4 ZA OSS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 28mm F2	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 50mm F1.8	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A7M3	FE 85mm F1.4 GM	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Distagon T* FE 35mm F1.4 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar T* FE 35mm F2.8 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar® T* FE 55mm F1.8 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 10–18mm F4 OSS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
		E PZ 18–105mm F4 G OSS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 18–200mm F3.5–6.3 OSS LE	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 30mm f/1.4 DC DN	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 50mm f/1.4 DG	Camera and lens	√	-	No need to remove eyepiece cap		
Camera, lens and servo motor (for focus control)	√		-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side			



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A7M3	Tamron 28-75mm f/2.8	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
	sigma18-35mm f/1.8 DC HSM Art (Canon lens adapter)	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap			
		Camera, lens and servo motor (for focus control)	-					
		Camera, lens and servo motor (for zoom control)	-					

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A7R3	FE 16-35mm F2.8 GM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 16-35mm F4 ZAISS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 12-24mm F4 G	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24mm f1.4GM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24-70mm F2.8 GM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A7R3	FE 24-70mm F4 ZA OSS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 28mm F2	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 50mm F1.8	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 85mm F1.4 GM	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Distagon T* FE 35mm F1.4 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar T* FE 35mm F2.8 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar® T* FE 55mm F1.8 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 10-18mm F4 OSS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
		E PZ 18-105mm F4 G OSS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 18-200mm F3.5-6.3 OSS LE	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A7R3	Sigma 30mm f/1.4 DC DN	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap		
		Sigma 50mm f/1.4 DG	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap		
		Tamron 28-75mm f/2.8	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		sigma18-35mm f/1.8 DC HSM Art (Canon lens adapter)	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A7R4	FE 16-35mm F2.8 GM	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 16-35mm F4 ZAISS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 12-24mm F4 G	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24mm f1.4GM	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24-70mm F2.8 GM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A7R4	FE 24-70mm F4 ZA OSS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 28mm F2	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 50mm F1.8	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 85mm F1.4 GM	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Distagon T* FE 35mm F1.4 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar T* FE 35mm F2.8 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar® T* FE 55mm F1.8 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 10-18mm F4 OSS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
		E PZ 18-105mm F4 G OSS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 18-200mm F3.5-6.3 OSS LE	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A7R4	Sigma 30mm f/1.4 DC DN	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap		
		Sigma 50mm f/1.4 DG	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap		
		Tamron 28-75mm f/2.8	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		sigma18-35mm f/1.8 DC HSM Art (Canon lens adapter)	Camera and lens	√	-	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for focus control)	-				
			Camera, lens and servo motor (for zoom control)	-				

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A6600	FE 16-35mm F2.8 GM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 16-35mm F4 ZAISS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 12-24mm F4 G	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24mm f1.4GM	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24-70mm F2.8 GM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A6600	FE 24-70mm F4 ZA OSS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 28mm F2	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 50mm F1.8	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 85mm F1.4 GM	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Distagon T* FE 35mm F1.4 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar T* FE 35mm F2.8 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar® T* FE 55mm F1.8 ZA	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 10-18mm F4 OSS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
		E PZ 18-105mm F4 G OSS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 18-200mm F3.5-6.3 OSS LE	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A6600	Sigma 30mm f/1.4 DC DN	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 50mm f/1.4 DG	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Tamron28-75mm f/2.8	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		sigma18-35mm f/1.8 DC HSM Art (Canon lens adapter)	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A6500	FE 16-35mm F2.8 GM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 16-35mm F4 ZAISS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 12-24mm F4 G	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24mm f1.4GM	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
		FE 24-70mm F2.8 GM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera
Sony	A6500	FE 24-70mm F4 ZA OSS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 28mm F2	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 50mm F1.8	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 85mm F1.4 GM	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Distagon T* FE 35mm F1.4 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar T* FE 35mm F2.8 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar® T* FE 55mm F1.8 ZA	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 10-18mm F4 OSS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A6500	E PZ 18-105mm F4 G OSS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 18-200mm F3.5-6.3 OSS LE	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24-105mm F4 G OSS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 30mm f/1.4 DC DN	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 50mm f/1.4 DG	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Tamron28-75mm f/2.8	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		sigma18-35mm f/1.8 DC HSM Art (Canon lens adapter)	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A6400	FE 16-35mm F2.8 GM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 16-35mm F4 ZAISS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 12-24mm F4 G	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24mm f1.4GM	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24-70mm F2.8 GM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera
		FE 24-70mm F4 ZA OSS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 28mm F2	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 50mm F1.8	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 85mm F1.4 GM	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A6400	Distagon T* FE 35mm F1.4 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar T* FE 35mm F2.8 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar® T* FE 55mm F1.8 ZA	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 10–18mm F4 OSS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
		E PZ 18–105mm F4 G OSS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 18–200mm F3.5–6.3 OSS LE	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 30mm f/1.4 DC DN	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 50mm f/1.4 DG	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Tamron28-75mm f/2.8	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
Camera, lens and servo motor (for zoom control)	√		√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side			



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A6400	sigma18-35mm f/1.8 DC HSM Art (Canon lens adapter)	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A6300	FE 16-35mm F2.8 GM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 16-35mm F4 ZAISS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 12-24mm F4 G	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24mm f1.4GM	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24-70mm F2.8 GM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap		Roll axis slightly rub against the camera
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on either side	Roll axis slightly rub against the camera
		FE 24-70mm F4 ZA OSS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A6300	FE 28mm F2	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 50mm F1.8	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 85mm F1.4 GM	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Distagon T* FE 35mm F1.4 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar T* FE 35mm F2.8 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar® T* FE 55mm F1.8 ZA	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 10–18mm F4 OSS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
		E PZ 18–105mm F4 G OSS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 18–200mm F3.5–6.3 OSS LE	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 30mm f/1.4 DC DN	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A6300	Sigma 50mm f/1.4 DG	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Tamron28-75mm f/2.8	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		sigma18-35mm f/1.8 DC HSM Art (Canon lens adapter)	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A6100	FE 16-35mm F2.8 GM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 16-35mm F4 ZAISS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 12-24mm F4 G	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24mm f1.4GM	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A6100	FE 24-70mm F2.8 GM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera
		FE 24-70mm F4 ZA OSS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 28mm F2	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 50mm F1.8	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 85mm F1.4 GM	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Distagon T* FE 35mm F1.4 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar T* FE 35mm F2.8 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar® T* FE 55mm F1.8 ZA	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 10-18mm F4 OSS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
		E PZ 18-105mm F4 G OSS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A6100	E 18-200mm F3.5-6.3 OSS LE	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 30mm f/1.4 DC DN	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 50mm f/1.4 DG	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Tamron28-75mm f/2.8	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		sigma18-35mm f/1.8 DC HSM Art (Canon lens adapter)	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A6000	FE 16-35mm F2.8 GM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 16-35mm F4 ZAISS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A6000	FE 12-24mm F4 G	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24mm f1.4GM	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 24-70mm F2.8 GM	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length. Need to remove eyepiece cap	Servo zoom & focus motor installed on the left	Roll axis slightly rub against the camera
		FE 24-70mm F4 ZA OSS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 28mm F2	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 50mm F1.8	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		FE 85mm F1.4 GM	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Distagon T* FE 35mm F1.4 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar T* FE 35mm F2.8 ZA	Camera and lens	√	-	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sonnar® T* FE 55mm F1.8 ZA	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Sony	A6000	E 10-18mm F4 OSS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on the left	
		E PZ 18-105mm F4 G OSS	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		E 18-200mm F3.5-6.3 OSS LE	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 30mm f/1.4 DC DN	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Sigma 50mm f/1.4 DG	Camera and lens	√	√	No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Tamron28-75mm f/2.8	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		sigma18-35mm f/1.8 DC HSM Art (Canon lens adapter)	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
FUJIFILM	X-H1	XF 16-55mm f/2.8 R LM WR	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XF 18-55mm f/2.8-4 R OIS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XF 18-135mm f/3.5-5.6 R LM OIS WR	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XF 35mm f/2 R WR	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XF 56mm f/1.2 R	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XC 15-45mm f/3.5-5.6 OIS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Super EBC XF 23mm f/1.4 R	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
FUJIFILM	X-T2	XF 16-55mm f/2.8 R LM WR	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XF 18-55mm f/2.8-4 R OIS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XF 18-135mm f/3.5-5.6 R LM OIS WR	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XF 35mm f/2 R WR	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XF 56mm f/1.2 R	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XC 15-45mm f/3.5-5.6 OIS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Super EBC XF 23mm f/1.4 R	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
FUJIFILM	X-T3	XF 16-55mm f/2.8 R LM WR	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XF 18-55mm f/2.8-4 R OIS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XF 18-135mm f/3.5-5.6 R LM OIS WR	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XF 35mm f/2 R WR	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XF 56mm f/1.2 R	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XC 15-45mm f/3.5-5.6 OIS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Super EBC XF 23mm f/1.4 R	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
FUJIFILM	X-T30	XF 16-55mm f/2.8 R LM WR	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XF 18-55mm f/2.8-4 R OIS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XF 18-135mm f/3.5-5.6 R LM OIS WR	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XF 35mm f/2 R WR	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XF 56mm f/1.2 R	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XC 15-45mm f/3.5-5.6 OIS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Super EBC XF 23mm f/1.4 R	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
FUJIFILM	X-T100	XF 16-55mm f/2.8 R LM WR	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XF 18-55mm f/2.8-4 R OIS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XF 18-135mm f/3.5-5.6 R LM OIS WR	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XF 35mm f/2 R WR	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XF 56mm f/1.2 R	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		XC 15-45mm f/3.5-5.6 OIS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Super EBC XF 23mm f/1.4 R	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/Focus Motor	Installation Remark
Panasonic	GH5s	Vario-Elmarit 8-18mm f/2.8-4.0	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Vario 12-35mm f/2.8 II	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Lumix G 25mm f/1.7	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		MACRO 30mm f/2.8	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		sigma 18-35mm f/1.8 DC HSM Art (+转接环)	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Panasonic	GH5	Vario-Elmarit 8-18mm f/2.8-4.0	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Vario 12-35mm f/2.8 II	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		Lumix G 25mm f/1.7	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		MACRO 30mm f/2.8	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
		sigma 18-35mm f/1.8 DC HSM Art (+转接环)	Camera and lens	√	√	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
Camera, lens and servo motor (for zoom control)	√		√	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side			

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
Panasonic	S1	LUMIX S 24-105mm F/4 Macro OIS	Camera and lens	√	-	Can be balanced at any focal length; No need to remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
			Camera, lens and servo motor (for zoom control)	√	-	Can be balanced at any focal length; No need to remove eyepiece cap	Servo zoom & focus motor installed on either side	
	S1H (TransMount Multifunctional Extension Plate required)	LUMIX S 24-105mm F/4 Macro OIS	Camera and lens	√	-	Can be balanced between focal length 24mm; Do not remove eyepiece cap	Can't install Servo zoom & focus motor	100g counterweight required



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
BMD	BMPCC 4K (TransMount Multifunctional Extension Plate required)	Vario-Elmarit 8-18mm f/2.8-4.0	Camera and lens	-		Do not remove eyepiece cap		100g counterweight required
			Camera, lens and servo motor (for focus control)	-		Do not remove eyepiece cap	Servo zoom & focus motor installed on the right	100g counterweight required
			Camera, lens and servo motor (for zoom control)	-		Do not remove eyepiece cap	Servo zoom & focus motor installed on the right	100g counterweight required
		Vario 12-35mm f/2.8 II	Camera and lens	-		Do not remove eyepiece cap		100g counterweight required
			Camera, lens and servo motor (for focus control)	-		Do not remove eyepiece cap	Servo zoom & focus motor installed on the right	100g counterweight required
			Camera, lens and servo motor (for zoom control)	-		Do not remove eyepiece cap	Servo zoom & focus motor installed on the right	100g counterweight required
		25mm f/1.7	Camera and lens	√	-	Do not remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Do not remove eyepiece cap	Servo zoom & focus motor installed on the right	
		MACRO 30mm f/2.8	Camera and lens	√	-	Do not remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Do not remove eyepiece cap	Servo zoom & focus motor installed on the right	
		D-Dreamer 12mm F2.8	Camera and lens	√	-	Do not remove eyepiece cap		100g counterweight required
			Camera, lens and servo motor (for focus control)	√	-	Do not remove eyepiece cap	Servo zoom & focus motor installed on the right	100g counterweight required



WEEBILL-S Camera Compatibility List

Camera Brand	Model	Lens Model	Mounting Status	Balance Adjustment	Camera Backing Base	Balance Adjustment with Camera and Lens Only	Servo Zoom/ Focus Motor	Installation Remark
BMD	BMPCC 6K (TransMount Multifunctional Extension Plate required)	EF 24mm f/1.4L II USM	Camera and lens	√	-	Do not remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Do not remove eyepiece cap	Servo zoom & focus motor installed on the right	
		EF 35mm f/1.4L II USM	Camera and lens	√	-	Do not remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Do not remove eyepiece cap	Servo zoom & focus motor installed on the right	
		EF 50mm f/1.4L USM	Camera and lens	√	-	Do not remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Do not remove eyepiece cap	Servo zoom & focus motor installed on the right	
		EF 85mm f/1.8L USM	Camera and lens	√	-	Do not remove eyepiece cap		
			Camera, lens and servo motor (for focus control)	√	-	Do not remove eyepiece cap	Servo zoom & focus motor installed on the right	